

Parallel Programming with MPI

MPI I Tutorial/Exercise (1)



It is God's privilege to conceal things, but the kings' pride is to research them.

(Proverbs 25:2; ascribed to King Solomon of Israel, BC 1000)

The 2nd KIAS CAC Summer School

June 30-July 2, 2011

Joo, Keehyoung (주기형) (newton@kias.re.kr)

Center for Advanced Computation (CAC)

Korea Institute for Advanced Study


Contents (MPI I)

- ❑ Background and Getting Started (1 hour)
- ❑ MPI Basic (1 hour)
- ❑ Intermediate MPI (1 hour)
- ❑ Applications / Comments (1 hour)

Scientific American : The Do-It-Yourself Supercomputer (August 2001)

Scientists have found a cheaper way to solve tremendously difficult computational problems:


connect ordinary PCs so that they can work together.



The First Beowulf cluster



- Thomas Sterling and Donald Becker CESDIS, Goddard Space Flight Center
- Summer 1994: built an experimental cluster
- Called their cluster "Beowulf"




- ❑ 16 x 486DX4, 100MHz processors
- ❑ 16MB of RAM each, 256MB in total
- ❑ Channel bonded Ethernet (2 x 10Mbps)
- ❑ Not that different from our cluster system

Parallel Programming with MPI I


Background and Getting Started (1 hour)

- Parallel Computing System
- Parallel Programming Concept
- What is MPI?
- Hello World !



Parallel Computing Systems

□ Multi Processor System (MP)




*Limited Scalability

*High Speed communication



□ Cluster System connected in Network



*High performance

*Large capacity

*High availability

*Incremental growth

*Network dependent communication


Network Comparison

	Fast Ethernet	Gigabit Ethernet	Myrinet	Infiniband
Latency	~100 μ s	~100 μ s	~2 μ s	~0.5 μ s ~2 μ s (mpi)
Bandwidth	~100Mbps peak	~1Gbps peak	~1.98Gbps real	~10 Gbyte/s real
Price	~50,000 W	~200,000 W	~800,000 W	~ ???
KIAS		life, fold, etc	quest	

▣ Normal PC Cluster rely on TCP/IP


- Real/MPI Latency is worse than the hardware latency
- Efficiency for short message is less than 50%
- Depends on Driver and NIC interaction

KIAS fold/life cluster system



Exercise : Login

Windows :
Xmanager



Linux or UNIX machines: Terminal Programs

```
% ssh guest@fold.kias.re.kr
```

```
% ssh -X guest@fold.kias.re.kr
```

Password:

kias!guest

Exercise : Linux Commands

```
% less /etc/motd
```

```
% less /proc/cpuinfo
```

```
% pestat
```

```
% df -h
```

```
% free
```

```
% ps ax
```

```
% pwd
```

```
% cat /etc/passwd
```

```
% echo $SHELL
```

```
% ls -l
```

```
% man ls
```

```
% ls -al
```

```
% less .bashrc
```

```
% cd MPI1
```

```
% ls -l
```

```
% cp -r examples newton
```


```
% cd newton
```

Compilers and Debuggers (serial)



- Languages : Fortran, C, C++, python, Java, etc
- GNU <http://www.gnu.org/>
 - % gcc
 - % g++
 - % gfortran
 - % gdb
- PGI <http://www.pgroup.com/>
 - % pgcc
 - % pgCC
 - % pgf77
 - % pgf90
 - % pgdbg
- Intel <http://developer.intel.com>
 - % icc
 - % ifort
 - % idb
- 실습
 - % cd MPI1/single
 - % gcc hello.c
 - % gfortran hello.f90

Parallel Computing & programming



- Separate workers or processes
- Interact by exchanging information

What is MPI ?

- **M P I** = **M**essage **P**assing **I**nterface
- Powerful, efficient, and *portable* way to express parallel *programs*
- Standard (specification)
 - Many implementations
 - Collection of **communication** library (subroutines)
- Two phases and... :
 - MPI 1: Traditional message-passing
 - MPI 2: Remote memory, parallel I/O, dynamic process
 - MPI 3: ???

Recommended Reading

- IBM RedBook
<http://www.redbooks.ibm.com/abstracts/sg245380.html>
- MPI를 이용한 병렬 프로그래밍 (KISTI)
- MPI 병렬프로그래밍 (이홍석 et. al. , 어드북스)
- LAM MPI Tutorial
<http://www.lam-mpi.org/tutorials/nd/>
- WWW
<http://www.cs.usfca.edu/mpi/>
<http://www.citutor.org/> Education site (Search MPI)
- Use Google ! with keyword "MPI programming", "Parallel Programming", ...

Message Passing Libraries

□ OpenMPI

- <http://www.open-mpi.org/>
- Very easy to use !



□ MPICH1 and 2

- <http://www.mcs.anl.gov/research/projects/mpich2/>
- Easy to use
- High portability



□ LAM MPI

- <http://www.lam-mpi.org/>
- High availability




Math library, Parallel Library

- Linpack/Lapack, ScaLapack
- Atlas (Automatic Tuned Linear Algebra software)
- Goto Library
- MKL (intel Math Kernel Library)
- GSL (GNU Scientific Library)
- FFT (Fast Fourier Transform)
- ETC ...

Parallel Programming Concept

□ Message Passing Interface



- (1) All processes execute the same program but each process is assigned a unique process id= 0,1,2,3,.....,(Nprocs-1)
- (2) Each process performs its own tasks assigned according to its process id

Simple Example #1 (Hello World)


```
#include <stdio.h>
#include "mpi.h"

int main (int argc, char **argv)
{
    int myrank, nprocs;

    MPI_Init (&argc, &argv);
    MPI_Comm_rank (MPI_COMM_WORLD, &myrank);
    MPI_Comm_size (MPI_COMM_WORLD, &nprocs);

    printf("Hello world! I am %d of %d\n", myrank, nprocs);

    MPI_Finalize ();
    return 0;
}
```



Simple Example #1 (Hello World)

Fortran 77 / 90

```
program hello

include 'mpif.h'      → use mpi      ! Fortran 90
integer myrank, nprocs
integer ierr

call MPI_INIT (ierr)
call MPI_COMM_RANK (MPI_COMM_WORLD, myrank, ierr)
call MPI_COMM_SIZE (MPI_COMM_WORLD, nprocs, ierr)

print *, "Hello world! I am ",myrank," of ",nprocs

call MPI_FINALIZE(ierr)

end program hello
```

Running your MPI programs

- Compile :
 - % cd newton/
 - % cat hello.c
 - % mpicc -o hello hello.c
 - % mpif90 -o hello hello.f90
- Running MPI Programs (OpenMPI):
 - % mpiexec -np 8 hello
 - % mpiexec -machinefile hosts -np 8 hello
- CPU time and Wall clock Time (Example #3 pi.f90)
 - % mpif90 -o pi pi.f90
 - % mpiexec -np 4 pi

Portable Batch System (PBS)

- ❑ Process and Resource Management
- ❑ Torque, openpbs
 - <http://www.clusterresources.com/products/torque-resource-manager.php>
- ❑ Commands (실습)
 - % qstat (Status)
 - % man qstat
 - % qstat -a
 - % qstat -u newton
 - % qstat -an
 - % qstat -q
 - % qstat -s
 - % qstat -f
 - % pestat (Node Status)
 - % qsub
 - % qdel
- ❑ PBS script (실습과 함께)

PBS Scripts

```
#!/bin/sh
#### Job name
#PBS -N JOB_NAME
#### Declare job non-rerunnable
#PBS -r n
#### Output files
#PBS -j oe
#### Mail to user
#PBS -m ae
#### Queue name (n2, n4, n16, n32, n64)
#PBS -q n32
#### Walltime limit (hh:mm:ss)
#PBS -l walltime=168:00:00

# This job's working directory
echo Working directory is $PBS_O_WORKDIR
cd $PBS_O_WORKDIR

echo Running on host `hostname`
echo Time is `date`
echo Directory is `pwd`
echo This job runs on the following processors:
echo `cat $PBS_NODEFILE`
# Define number of processors
NPROCS=`wc -l < $PBS_NODEFILE`
```

```
## your parallel job

mpiexec -np $NPROCS a.out
```

```
* PBS interactive mode
% qsub -I -q n8 -N job_name
% qsub -I -q n16 -N job_name

% echo $PBS_O_WORKDIR
% echo $PBS_NODEFILE
% cat $PBS_NODEFILE
% export | grep PBS

* PBS commands
% cat start.mat
% qsub start.mat
% qdel 57480
```

Learning MPI

- MPI is large (about 125 functions)
 - MPI's extensive functionality requires many functions
 - Number of functions not necessarily a measure of complexity
- MPI is small (6 functions + sum of them~)
 - Many parallel programs can be written with just 8 basic functions
- MPI is just right
 - One can access flexibility when it is required
 - One need not master all parts of MPI to use it.

Basic MPI Functions (C)

□ Init

`MPI_Init(&argc, &argv)`

`MPI_Comm_size(MPI_COMM_WORLD, &nprocs)`

`MPI_Comm_rank(MPI_COMM_WORLD, &rank)`

□ Message Passsing

`MPI_Send(...)` point to point communication

`MPI_Recv(...)`

`MPI_Bcast(...)` collective communication

`MPI_Reduce(...)`

□ Finalize

`MPI_Finalize()`

Basic MPI Functions (Fortran)

□ Init

Call MPI_Init(ierr)

Call MPI_Comm_size(MPI_COMM_WORLD, nprocs, ierr)

Call MPI_Comm_rank(MPI_COMM_WORLD, myrank, ierr)

□ Message Passing

Call MPI_Send(...) point to point communication

Call MPI_Recv(...)

Call MPI_Bcast(...) collective communication

Call MPI_Reduce(...)

□ Finalize

Call MPI_Finalize(ierr)

Types of parallel programming

□ Coarse-Grained Parallel Applications:

Monte Carlo Simulations, 3D Graphics rendering,
Database Search Problems (Web Search Engine),
Embarrassingly Parallel Programs.

□ Medium-grained Parallel Applications:

Divide & Conquer style analysis,
Domain decomposition Methods.

□ Fine-grained parallel applications:


Parallel Mandelbrot set

- A Mandelbrot set is a set of points in the complex plane
- Computed by the recursive function

$$z_{k+1} = z_k^2 + c$$

c is a complex number which gives the position of a point in the complex plane

z_{k+1} is the $(k+1)$ th iteration of the complex number $z = a+bi$
the initial value for z is 0



실습:

```
% cd Mandel
```

```
% ./run.sh 8
```

Povray on Linux Cluster

<http://www.povray.com>



- POV-Ray (Persistence Of Vision RAYtracer) is a high-quality tool for creating three-dimensional graphics.
- Raytraced images are publication-quality and 'photo-realistic'.
- but are computationally expensive so that large images can take many hours to create.

실습:

```
% cd povray/example
```





```
% ./povray.single woodbox.pov
```

```
% ./run.sh
```



Other Applications...


- Visualize / Weather
- Media Encoding (Image compress, DVD, MP3, ETC...)
- Internet Server (Web, Database)
- Science, etc...



Parallel Programming with MPI I

MPI Basics (1 hour)

- Point to Point Communication (blocking Send/Recv)
- Some of collective communication



Basic MPI Functions (Fortran)

□ Init

Call MPI_Init(ierr)

Call MPI_Comm_size(MPI_COMM_WORLD, nprocs, ierr)

Call MPI_Comm_rank(MPI_COMM_WORLD, myrank, ierr)

□ Message Passing

Call MPI_Send(...) point to point communication

Call MPI_Recv(...)


Call MPI_Bcast(...) collective communication

Call MPI_Reduce(...)

□ Finalize

Call MPI_Finalize(ierr)

Point to Point Communication



Message



MPI Send / Recv

*Data:

buffer, count, datatype

*Envelope:

process identifier (src/dest)

message tag

communicator

Point to Point Communication (C)

MPI_Send(buf, count, datatype, dest, tag, comm);

- buf : Send buffer
- count : Number of sent elements
- datatype : MPI datatype
- dest : Destination Process ID
- tag : Message tag
- comm : Communicator

MPI_Recv(buf, count, datatype, source, tag, comm, &status);

- buf : Receive Buffer
- source : Source Process ID
- status : Receive status

Point to Point Communication (Fortran)

Call MPI_SEND(buf, count, datatype, dest, tag, comm, ierr);

- buf : Send buffer
- count : Number of sent elements
- datatype : MPI datatype
- dest : Destination Process ID
- tag : Message tag
- comm : Communicator

Call MPI_RECV(buf, count, datatype, source, tag, comm, status, ierr);

- buf : Receive Buffer
- source : Source Process ID
- status : Receive status

Fortran

```

program hello2
  use mpi
  implicit none
  integer irank, nprocs, ierr, i
  integer tag
  integer istatus(MPI_STATUS_SIZE)
  character*100 msg

  call MPI_INIT(ierr)
  call MPI_COMM_RANK(MPI_COMM_WORLD, irank, ierr)
  call MPI_COMM_SIZE(MPI_COMM_WORLD, nprocs, ierr)

  tag = 10
  if (irank == 0) then
    write(msg, '(A,2x,I2)') 'Hello! node 2'
    idest = 1
    call MPI_SEND(msg,100, MPI_CHARACTER, idest, tag, MPI_COMM_WORLD, ierr)
  else
    isrc = 0
    call MPI_RECV(msg,100, MPI_CHARACTER, isrc, tag, MPI_COMM_WORLD, istatus, ierr)
    write(6, '(A)') trim(msg)
    write(6, '(A)') 'Hi ~'
  endif

  call MPI_FINALIZE(ierr)
end program hello2

```

* Example (hello2.f90)

% mpicc hello2.f90

% mpiexec -np 2 ./a.out

% mpiexec -np 4 ./a.out

(dead lock?)

C

```

#include <stdio.h>
#include "mpi.h"
// hello2
int main (int argc, char **argv)
{
  int rank, size;
  int tag;
  int dest, src;
  char msg[100];
  MPI_Status status;

  MPI_Init (&argc, &argv);
  MPI_Comm_rank (MPI_COMM_WORLD, &rank);
  MPI_Comm_size (MPI_COMM_WORLD, &size);

  tag = 123;
  if (rank == 0) {
    sprintf(msg, "Hello! node 2");
    dest= 1;
    MPI_Send(msg,100,MPI_CHAR, dest, tag, MPI_COMM_WORLD);
  }
  else {
    src = 0;
    MPI_Recv(msg,100,MPI_CHAR, src, tag, MPI_COMM_WORLD,&status);
    printf("%s\n", msg);
    printf("=> Hi ~\n");
  }

  MPI_Finalize ();
}

```

* Example (hello2.c)

% mpicc hello2.f90

% mpiexec -np 2 ./a.out

% mpiexec -np 4 ./a.out

(dead lock?)

Fortran

```
program hello3
  use mpi
  implicit none
  integer ierr, irank, nprocs
  integer tag, num, next, prev
  integer istatus(MPI_STATUS_SIZE)
  integer i
  character*100 msg

  call MPI_INIT(ierr)
  call MPI_COMM_RANK(MPI_COMM_WORLD, irank, ierr)
  call MPI_COMM_SIZE(MPI_COMM_WORLD, nprocs, ierr)

  tag = 10
  if (irank == 0) then
    do i=1, nprocs-1
      write(msg, '(A,2x,I2)') 'Hello! node', i
      call MPI_SEND(msg, 100, MPI_CHARACTER, i, tag, MPI_COMM_WORLD, ierr)
    end do
  else
    call MPI_RECV(msg, 100, MPI_CHARACTER, 0, tag, MPI_COMM_WORLD, istatus, ierr)
    write(6, '(A)') trim(msg)
  endif

  call MPI_FINALIZE(ierr)
end program hello3
```

* hello3: for all nodes

C

```
#include <stdio.h>
#include "mpi.h"
// hello4
int main (int argc, char **argv)
{
  int rank, size;
  int tag;
  int dest, src, man;
  char msg[100];
  MPI_Status status;

  MPI_Init (&argc, &argv);
  MPI_Comm_rank (MPI_COMM_WORLD, &rank);
  MPI_Comm_size (MPI_COMM_WORLD, &size);

  tag = 123;
  if (rank == 0) {
    for (dest=1; dest < size; dest++) {
      sprintf(msg, "Hello! node %d", dest);
      MPI_Send(msg, 100, MPI_CHAR, dest, tag, MPI_COMM_WORLD);
    }
  }
  else {
    src = 0;
    MPI_Recv(msg, 100, MPI_CHAR, src, tag, MPI_COMM_WORLD, &status);
    printf("%s\n", msg);
    man = status.MPI_SOURCE;
    printf("=> Hi, master %d ~\n", man);
  }

  MPI_Finalize ();
}
```

* hello4: with **MPI_SOURCE**

MPI Data Type

Call **MPI_Send** (**buf**, **count**, **datatype**, **dest**, **tag**, **comm**)

Call **MPI_Recv** (**buf**, **count**, **datatype**, **source**, **tag**, **comm**, **status**)

C Data Types		Fortran Data Types	
MPI_CHAR	signed char	MPI_CHARACTER	character(1)
MPI_SHORT	signed short int		
MPI_INT	signed int	MPI_INTEGER	integer
MPI_LONG	signed long int		
MPI_UNSIGNED_CHAR	unsigned char		
MPI_UNSIGNED_SHORT	unsigned short int		
MPI_UNSIGNED	unsigned int		
MPI_UNSIGNED_LONG	unsigned long int		
MPI_FLOAT	float	MPI_REAL	real
MPI_DOUBLE	double	MPI_DOUBLE_PRECISION	double precision
MPI_LONG_DOUBLE	long double		
		MPI_COMPLEX	complex
		MPI_DOUBLE_COMPLEX	double complex
		MPI_LOGICAL	logical
MPI_BYTE	8 binary digits	MPI_BYTE	8 binary digits
MPI_PACKED	data packed or unpacked with MPI_Pack()/MPI_Unpack	MPI_PACKED	data packed or unpacked with MPI_Pack()/MPI_Unpack

Retrieving further information

- Status is a data structure allocated in the user's program.

- **in C**

`MPI_Recv(..., MPI_ANY_SOURCE, MPI_ANY_TAG, ..., &status);`

`tag = status.MPI_TAG`

`src = status.MPI_SOURCE`

`MPI_Get_count (&status, datatype, &cnt);`

- **in Fortran**

`call MPI_RECV(...,MPI_ANY_SOURCE, MPI_ANY_TAG,...status,...)`

`itag = status (MPI_TAG)`

`isrc = status (MPI_SOURCE)`

`call MPI_GET_COUNT(status,datatype,icnt, ierr)`

* retrieve.f90

```

program main
  use mpi

  integer irank, nproc, itag, i, ierr
  integer isrc, idst, source
  integer my_src, my_tag, my_cnt
  integer istatus (MPI_STATUS_SIZE)
  real*8 data(10)

  call MPI_INIT (ierr)
  call MPI_COMM_RANK (MPI_COMM_WORLD, irank, ierr)
  call MPI_COMM_SIZE (MPI_COMM_WORLD, nproc, ierr)

  print *, 'Process ', irank, ' of ', nproc, ' is alive'

  if (irank == 0) then
    do i = 1, 10
      data(i) = i
    enddo
    idst = 1
    call MPI_SEND (data,10,MPI_REAL8, idst, 2011,MPI_COMM_WORLD,ierr)
  else if (irank == 1) then
    itag = MPI_ANY_TAG
    source = MPI_ANY_SOURCE
    call MPI_RECV (data,10,MPI_REAL8, source, itag, MPI_COMM_WORLD,istatus,ierr)

    my_src = istatus(MPI_SOURCE)
    my_tag = istatus(MPI_TAG)

    call MPI_GET_COUNT (istatus,MPI_REAL8, my_cnt, ierr)

    print *, 'status info: source = ', my_src
    print *, 'tag = ', my_tag
    print *, 'count = ', my_cnt
  else
    continue
  endif

  call MPI_FINALIZE (ierr)
end program main

```

Fortran:
retriev.f90

```

program pi_calculation
  use mpi

  real*8, parameter :: PI25DT = 3.141592653589793238462643d0
  real*8 pi_node, pi, h, sum, x, f, a
  integer n, irank, nprocs, i, rc
  integer istat(MPI_STATUS_SIZE)
  real*4 time_start, time_end, elapsed_time, total_time
  real*8 stime, etime

  ! function to integrate
  f(x) = 4.d0 / (1.d0 + x*x)

  call MPI_INIT( ierr )
  call MPI_COMM_RANK( MPI_COMM_WORLD, irank, ierr )
  call MPI_COMM_SIZE( MPI_COMM_WORLD, nprocs, ierr )

  if ( irank == 0 ) then
    write(6,'(A,$)') 'Enter the number of intervals = '
    read *, n
    do i=1, nprocs-1
      call MPI_SEND(n,1,MPI_INTEGER,i,123,MPI_COMM_WORLD,ierr)
    enddo
  else
    call MPI_RECV(n,1,MPI_INTEGER,0,123,MPI_COMM_WORLD,istat,ierr)
  endif

  stime= MPI_WTIME ()
  call cpu_time (time_start)


  ! calculate the interval size and pi_node
  h = 1.0d0/n
  sum = 0.0d0

  do i = irank+1, n, nprocs
    x = h * (dble(i) - 0.5d0)
    sum = sum + f(x)
  enddo
  pi_node = h * sum

  call cpu_time(time_end)
  elapsed_time = time_end-time_start

```

* PI Calculation



* pi_comm.f90

```

! collect all the partial sums
if ( irank == 0 ) then
  pi = pi_node
  do i=1, nprocs-1
    call MPI_RECV(pi_node,1,MPI_REAL8,i,345,MPI_COMM_WORLD,istat,ierr)
    pi = pi + pi_node
    call MPI_RECV(elapsed_time,1,MPI_REAL,i,678,MPI_COMM_WORLD,istat,ierr)
    total_time = total_time + elapsed_time
  enddo
else
  call MPI_SEND(pi_node,1,MPI_REAL8,0,345,MPI_COMM_WORLD,ierr)
  call MPI_SEND(elapsed_time,1,MPI_REAL,0,678,MPI_COMM_WORLD,ierr)
endif

etime= MPI_WTIME ()


write(6, *) 'My elapsed time (',irank,') =',elapsed_time, ' seconds'
if (irank .eq. 0) then
  write(6, *)
  write(6, 97) pi, abs(pi - PI25DT)
  97 format('PI is approximately: ', F18.16, ' Error is: ', F18.16)
  write(6, *) 'Wall Clock Time =', etime-stime, ' seconds'
  write(6, *) 'Total Cpu Time  =', total_time, ' seconds'
  write(6, *) 'Speed up      =', total_time/(etime-stime)
  write(6, *) 'The number of Processors =', nprocs
endif

call MPI_FINALIZE(ierr)
end program pi_calculation

```

Some of Collective Communication

□ Broadcast



In C:


`MPI_Bcast (&buf,count,datatype,root, comm);`

In Fortran:

`Call MPI_BCAST (buf,count,datatype,root, comm,ierr)`

Some of Collective Communication

Reduce



In C:

`MPI_Reduce (&sendbuf,&recvbuf,count,datatype,operator,root, comm);`

In Fortran:

Call `MPI_BCAST (sendbuf,recvbuf,count,datatype,operator,root, comm,ierr)`

Barrier : create a barrier synchronization

`MPI_Barrier (comm);`

Call `MPI_BARRIER(comm,ierr)`

```

program pi_calculation
  use mpi

  real*8, parameter :: PI25DT = 3.141592653589793238462643d0
  real*8 pi_node, pi, h, sum, x, f, a
  integer n, irank, nprocs, i, rc
  integer istat(MPI_STATUS_SIZE)
  real*4 time_start, time_end, elapsed_time, total_time
  real*8 stime, etime

  ! function to integrate
  f(x) = 4.d0 / (1.d0 + x*x)


  call MPI_INIT( ierr )
  call MPI_COMM_RANK( MPI_COMM_WORLD, irank, ierr )
  call MPI_COMM_SIZE( MPI_COMM_WORLD, nprocs, ierr )

  if ( irank == 0 ) then
    write(6, '(A,$)') 'Enter the number of intervals = '
    read *, n
  endif
  call MPI_BCAST(n,1,MPI_INTEGER,0,MPI_COMM_WORLD,ierr)

  stime= MPI_WTIME ()
  call cpu_time (time_start)

```

* PI Calculation



* pi_reduce.f90

```

  if ( irank == 0 ) then
    write(6, '(A,$)') 'Enter the number of intervals = '
    read *, n
    do i=1, nprocs-1
      call MPI_SEND(n,1,MPI_INTEGER,i,123,MPI_COMM_WORLD,ierr)
    enddo
  else
    call MPI_RECV(n,1,MPI_INTEGER,0,123,MPI_COMM_WORLD,istat,ierr)
  endif

```

```

! calculate the interval size and pi_node
h = 1.0d0/n
sum = 0.0d0

do i = irank+1, n, nprocs
  x = h * (dble(i) - 0.5d0)
  sum = sum + f(x)
enddo
pi_node = h * sum

call cpu_time(time_end)
elapsed_time = time_end-time_start

! collect all the partial sums
call MPI_REDUCE(pi_node,pi,1,MPI_REAL8,MPI_SUM,0,MPI_COMM_WORLD,ierr)
call MPI_REDUCE(elapsed_time,total_time,1,MPI_REAL4,MPI_SUM,0,MPI_COMM_WORLD,ierr)

etime= MPI_WTIME ()

write(6, *) 'My elapsed time (' ,irank,') =' ,elapsed_time, ' seconds'
if (irank .eq. 0) then
  write(6, *)
  write(6, 97) pi, abs(pi - PI25DT)
  97 format('PI is approximately: ', F18.16, ' Error is: ', F18.16)
  write(6, *) 'Wall Clock Time =' , etime-stime, ' seconds'
  write(6, *) 'Total Cpu Time =' , total_time, ' seconds'
  write(6, *) 'Speed up =' , total_time/(etime-stime)
  write(6, *) 'The number of Processors =' , nprocs
endif

call MPI_FINALIZE(ierr)
end program pi calculation

```

MPI Reduce Operators

MPI Reduction Operation		C Data Types	Fortran Data Type
MPI_MAX	maximum	integer, float	integer, real, complex
MPI_MIN	minimum	integer, float	integer, real, complex
MPI_SUM	sum	integer, float	integer, real, complex
MPI_PROD	product	integer, float	integer, real, complex
MPI_LAND	logical AND	integer	logical
MPI_BAND	bit-wise AND	integer, MPI_BYTE	integer, MPI_BYTE
MPI_LOR	logical OR	integer	logical
MPI_BOR	bit-wise OR	integer, MPI_BYTE	integer, MPI_BYTE
MPI_LXOR	logical XOR	integer	logical
MPI_BXOR	bit-wise XOR	integer, MPI_BYTE	integer, MPI_BYTE
MPI_MAXLOC	max value and location	float, double and long double	real, complex, double precision
MPI_MINLOC	min value and location	float, double and long double	real, complex, double precision

Basic MPI Functions (Fortran)

- Init

Call MPI_Init(ierr)

Call MPI_Comm_size(MPI_COMM_WORLD, nprocs, ierr)

Call MPI_Comm_rank(MPI_COMM_WORLD, myrank, ierr)

- Message Passing

Call MPI_Send(...) point to point communication

Call MPI_Recv(...)

Call MPI_Bcast(...) collective communication

Call MPI_Reduce(...)

- Finalize

Call MPI_Finalize(ierr)

```
program workshare
  use mpi
  integer irank, nprocs, ierr
  integer n, istart, iend
  integer*8 isum, itotal

  call MPI_INIT (ierr)
  call MPI_COMM_RANK (MPI_COMM_WORLD, irank, ierr)
  call MPI_COMM_SIZE (MPI_COMM_WORLD, nprocs, ierr)
  if (irank == 0) then
    write(6,'(A,$)') ' Enter the number of your jobs = '
    read *, n
  endif
  call MPI_BCAST(n,1,MPI_INTEGER,0,MPI_COMM_WORLD,ierr)
  call para_range(1,n, nprocs, irank, istart, iend)

  isum = 0
  do i= istart, iend
    isum = isum + i
  enddo
  write(6,10) 'I am node ', irank, ' my range = ', istart,iend, 'my sum =', isum
  10 format(A,I3,A,2I12,2x,A,I14)

  call MPI_REDUCE (isum,itotal,1,MPI_INTEGER8,MPI_SUM,0,MPI_COMM_WORLD,ierr)
  if (irank == 0) then
    write(6,'(A,2x,I14)') 'Total sum = ', itotal
  endif
  call MPI_FINALIZE(ierr)
end program workshare

subroutine para_range(n1, n2, nprocs, irank, ista, iend)
  integer n1,n2,nprocs,irank,ista,iend
  integer iwork1, iwork2
  iwork1 = (n2 - n1 + 1) / nprocs
  iwork2 = MOD(n2 - n1 + 1, nprocs)
  ista = irank * iwork1 + n1 + MIN(irank, iwork2)
  iend = ista + iwork1 - 1
  IF (iwork2 > irank) iend = iend + 1
end
```

* workshare.f90
-load balancing
-fine grain...



```

#include <stdio.h>
#include "mpi.h"
#define MIN(a,b) ((a) < (b) ? (a) : (b))
// workshare
void para_range(int n1,int n2,int nprocs,int rank,int *start,int *end);

int main (int argc, char **argv)
{
    int rank, nprocs;
    int i, n, start, end;
    unsigned long int sum, total;

    MPI_Init (&argc, &argv);
    MPI_Comm_rank (MPI_COMM_WORLD, &rank);
    MPI_Comm_size (MPI_COMM_WORLD, &nprocs);
    if (rank == 0) {
        printf(" Enter the number of your jobs = \n");
        scanf("%d",&n);
    }
    MPI_Bcast (&n,1,MPI_INT,0,MPI_COMM_WORLD);
    para_range(1,n,nprocs, rank, &start, &end);

    sum = 0;
    for (i=start; i<= end; i++) {
        sum += i;
    }
    printf("I am node %d my range = %d %d my sum = %ld\n",
        rank, start, end, sum);

    MPI_Reduce(&sum,&total,1,MPI_UNSIGNED_LONG,MPI_SUM,0,MPI_COMM_WORLD);
    if (rank == 0) {
        printf("Total sum = %ld\n",total);
    }
    MPI_Finalize ();
}

void para_range(int n1,int n2,int nprocs,int rank,int *start,int *end){
    int iwork1, iwork2;
    iwork1 = (n2 - n1 + 1) / nprocs;
    iwork2 = (n2 - n1 + 1) % nprocs;
    *start = rank * iwork1 + n1 + MIN (rank, iwork2);
    *end = *start + iwork1 - 1 ;
    if (iwork2 > rank) *end = *end + 1;
}


```

* workshare.c
 -load balancing
 -fine grain...


Parallel Programming with MPI I

Intermediate MPI and ... (2 hour)

- non-Blocking Send/Recv
- Collective Communications
- Applications / Comments



non-Blocking Send/Recv (Ex)



Non-blocking operations allow overlapping computation and communication.

Blocking/non-Blocking Send/Recv

In C :

MPI_request request;

□ Blocking (Send/Recv)

MPI_Send (buf, count, datatype, dest, tag, comm);

MPI_Recv (buf, count, datatype, source, tag, comm, &status);

□ non-Blocking (Isend/Irecv)

MPI_Isend (buf, count, datatype, dest, tag, comm, &request);

MPI_Irecv (buf, count, datatype, source, tag, comm, &request);

MPI_Wait (&request, &status);

* hello5, 6, 7

Blocking/non-Blocking Send/Recv

In Fortran :

integer request

□ Blocking (Send/Recv)

Call `MPI_SEND (buf, count, datatype, dest, tag, comm)`

Call `MPI_RECV (buf, count,datatype,source, tag, comm, status)`

□ non-Blocking (Isend/Irecv)

Call `MPI_ISEND (buf, count, datatype, dest, tag, comm, request)`

Call `MPI_IRECV (buf, count,datatype,source, tag, comm, request)`

Call `MPI_WAIT (request, status)`

* hello5, 6, 7

```
#include <stdio.h>
#include "mpi.h"
// hello5
int main (int argc, char **argv)
{
    int rank, size;
    int tag;
    int dest, src, man;
    char msg[100];
    MPI_Status status;
    MPI_Request req;

    MPI_Init (&argc, &argv);
    MPI_Comm_rank (MPI_COMM_WORLD, &rank);
    MPI_Comm_size (MPI_COMM_WORLD, &size);

    tag = 123;
    if (rank == 0) {
        for (dest=1; dest < size; dest++) {
            sprintf(msg,"Hello! node %d",dest);
            MPI_Isend(msg,100,MPI_CHAR, dest, tag, MPI_COMM_WORLD,&req);
        }
    }
    else {
        src = 0;
        MPI_Recv(msg,100,MPI_CHAR, src , tag, MPI_COMM_WORLD,&status);
        printf("%s\n", msg);
        man = status.MPI_SOURCE;
        printf("=> Hi, master %d ~\n",man);
    }

    MPI_Finalize ();
}
```

* hello5.c : MPI_Isend

```

#include <stdio.h>
#include "mpi.h"
// hello6
int main (int argc, char **argv)
{
    int rank, size;
    int tag;
    int dest, src, man;
    char msg[100];
    MPI_Status stat1, stat2;
    MPI_Request req1, req2;

    MPI_Init (&argc, &argv);
    MPI_Comm_rank (MPI_COMM_WORLD, &rank);
    MPI_Comm_size (MPI_COMM_WORLD, &size);
    tag = 123;
    if (rank == 0) {
        for (dest=1; dest < size; dest++) {
            sprintf(msg, "Hello! node %d", dest);
            MPI_Isend(msg, 100, MPI_CHAR, dest, tag, MPI_COMM_WORLD, &req1);
        }
    }
    else {
        src = 0;
        MPI_Irecv(msg, 100, MPI_CHAR, src, tag, MPI_COMM_WORLD, &req2);
    }
    MPI_Wait(&req1, &stat1);
    MPI_Wait(&req2, &stat2);

    if (rank != 0) {
        printf("%s\n", msg);
        man = stat2.MPI_SOURCE;
        printf("=> Hi, master %d ~\n", man);
    }
    MPI_Finalize ();
}

```

* hello6.c

MPI_Isend, MPI_Irecv


MPI_Wait

```

program hello7
    use mpi
    implicit none
    integer ierr, irank, nprocs
    integer tag, num, next, prev
    integer ireq1, ireq2
    integer istat1(MPI_STATUS_SIZE), istat2(MPI_STATUS_SIZE)
    integer man, i
    character*100 msg, msg2, msgs(500)
    call MPI_INIT(ierr)
    call MPI_COMM_RANK(MPI_COMM_WORLD, irank, ierr)
    call MPI_COMM_SIZE(MPI_COMM_WORLD, nprocs, ierr)
    tag = 123
    if (irank == 0) then
        do i=1, nprocs-1
            write(msg, '(A,2x,I2)') 'Hello! node', i
            call MPI_ISEND(msg, 100, MPI_CHARACTER, i, tag, MPI_COMM_WORLD, ireq1, ierr)
        end do
        do i=1, nprocs-1
            call MPI_Irecv(msgs(i), 100, MPI_CHARACTER, i, tag, MPI_COMM_WORLD, ireq2, ierr)
        end do
    else
        call MPI_Irecv(msg, 100, MPI_CHARACTER, 0, tag, MPI_COMM_WORLD, ireq2, ierr)
        write(msg2, '(A,2x,I2)') "Hi, master~ I'm node ", irank
        call MPI_ISEND(msg2, 100, MPI_CHARACTER, 0, tag, MPI_COMM_WORLD, ireq1, ierr)
    endif
    call MPI_WAIT (ireq1, istat1, ierr)
    call MPI_WAIT (ireq2, istat2, ierr)
    if (irank == 0) then
        do i=1, nprocs-1
            write(6, '(A)') trim(msgs(i))
        end do
    else
        write(6, '(A)') trim(msg)
    endif
    call MPI_FINALIZE(ierr)
end program hello7

```

* bi-directional
communication
* hello7.f90



Synchronization

MPI_Barrier (comm)



Call **MPI_Barrier (comm, ierr)**

in **C**







in **Fortran**

- Blocks until all processes in the group of the communicator **comm** call it.
- Almost never required in a parallel program
 - Occasionally useful in measuring performance and load balancing


Collective Communications



-MPI_BCAST
-MPI_GATHER
-MPI_ALLGATHER
-MPI_REDUCE
-MPI_ALLREDUCE



Scatter & Gather



In C:

```
MPI_Scatter (&sendbuf, sendcount, sendtype,
             &recvbuf, recvcount, recvtype, root, comm);
MPI_Gather (&sendbuf, sendcount, sendtype,
            &recvbuf, recvcount, recvtype, root, comm);
```

In Fortran:

```
Call MPI_SCATTER (sendbuf, sendcount, sendtype,
                  recvbuf, recvcount, recvtype, root, comm, ierr);
Call MPI_GATHER (sendbuf, sendcount, sendtype,
                 recvbuf, recvcount, recvtype, root, comm, ierr);
```

```
#include <stdio.h>
#include "mpi.h"
#include "nrutil.h"
#define MIN(a,b) ((a) < (b) ? (a) : (b))
// gather
void para_range(int n1, int n2, int nprocs, int rank, int *start, int *end);

int main (int argc, char **argv)
{
    int rank, nprocs;
    int i, n, start, end;
    unsigned long *val;
    unsigned long sum, total;

    MPI_Init (&argc, &argv);
    MPI_Comm_rank (MPI_COMM_WORLD, &rank);
    MPI_Comm_size (MPI_COMM_WORLD, &nprocs);


    if (rank == 0) {
        val = lvector(0, nprocs-1);
        printf(" Enter the number of your jobs = \n");
        scanf("%d", &n);
    }
    MPI_Bcast (&n, 1, MPI_INT, 0, MPI_COMM_WORLD);
    para_range(1, n, nprocs, rank, &start, &end);

    sum = 0;
    for (i=start; i<= end; i++) {
        sum += i;
    }
    MPI_Gather(&sum, 1, MPI_UNSIGNED_LONG,
              val, 1, MPI_UNSIGNED_LONG, 0, MPI_COMM_WORLD);
    if (rank == 0) {
        total = 0;
        for (i=0; i<nprocs; i++) {
            printf(" node %d sum = %ld\n", i, val[i]);
            total += val[i];
        }
        printf("Total sum = %ld\n", total);
    }
    MPI_Finalize ();
}
```

*** gather.c**

% mpicc -c nrutil.c

% mpicc gather.c nrutil.o



*** count = 1**

```

program gather
use mpi
integer irank, nprocs, ierr
integer n, istart, iend
integer*8 isum
integer*8, allocatable :: ival(:)


call MPI_INIT (ierr)
call MPI_COMM_RANK (MPI_COMM_WORLD, irank, ierr)
call MPI_COMM_SIZE (MPI_COMM_WORLD, nprocs, ierr)
if (irank == 0) then
    allocate (ival(0:nprocs-1))
    write(6, '(A,$)') ' Enter the number of your jobs = '
    read *, n
endif
call MPI_BCAST(n,1,MPI_INTEGER,0,MPI_COMM_WORLD,ierr)
call para_range(1,n, nprocs, irank, istart, iend)

isum = 0
do i= istart, iend
    isum = isum + i
enddo
call MPI_GATHER(isum,1,MPI_INTEGER8, 0,
                ival,1,MPI_INTEGER8,0,MPI_COMM_WORLD,ierr)

if (irank == 0) then
    do i=0, nprocs-1
        write(6, '(A,2x,I2,2x,A,I14)') 'node ',i,' sum =',ival(i)
    enddo
    write(6, '(A,2x,I14)') 'Total sum = ', sum(ival)
endif
call MPI_FINALIZE(ierr)
end program gather


```

* gather.f90



* count = 1

All Gather



In C:

```

MPI_Allgather (&sendbuf,sendcount,sendtype,
               &recvbuf,recvcount,recvtype,comm);

```

In Fortran:

```

Call MPI_ALLGATHER (sendbuf,sendcount,sendtype,
                    recvbuf,recvcount,recvtype,comm,ierr);

```

* allgather.c

```
#include <stdio.h>
#include "mpi.h"
#include "nrutil.h"
#define MIN(a,b) ((a) < (b) ? (a) : (b))
// allgather
void para_range(int n1,int n2,int nprocs,int rank,int *start,int *end);

int main (int argc, char **argv)
{
    int rank, nprocs;
    int i, j, n, start, end;
    unsigned long *val;
    unsigned long sum, total;

    MPI_Init (&argc, &argv);
    MPI_Comm_rank (MPI_COMM_WORLD, &rank);
    MPI_Comm_size (MPI_COMM_WORLD, &nprocs);

    val = lvector(0,nprocs-1);
    if (rank == 0) {
        printf(" Enter the number of your jobs = \n");
        scanf("%d",&n);
    }
    MPI_Bcast (&n,1,MPI_INT,0,MPI_COMM_WORLD);
    para_range(1,n,nprocs, rank, &start, &end);

    sum = 0;
    for (i=start; i<= end; i++) {
        sum += i;
    }
    MPI_Allgather(&sum,1,MPI_UNSIGNED_LONG,
                 val,1,MPI_UNSIGNED_LONG,MPI_COMM_WORLD);
    total = 0;
    for (i=0; i<nprocs ; i++) total += val[i];
    printf(" node %d sum = %ld ",rank,total);
    for (j=0; j<nprocs; j++) printf(" %ld",val[j]); printf("\n");

    MPI_Finalize ();
}
```

* count = 1
- no root

* allreduce.f90

```
program allreduce
    use mpi
    implicit none
    integer irank, nprocs, ierr
    integer n, istart, iend
    integer*8 isum, itot
    integer i,j

    call MPI_INIT (ierr)
    call MPI_COMM_RANK (MPI_COMM_WORLD, irank, ierr)
    call MPI_COMM_SIZE (MPI_COMM_WORLD, nprocs, ierr)
    if (irank == 0) then
        write(6,'(A,$)') ' Enter the number of your jobs = '
        read *, n
    endif
    call MPI_BCAST(n,1,MPI_INTEGER,0,MPI_COMM_WORLD,ierr)
    call para_range(1,n, nprocs, irank, istart, iend)


    isum = 0
    do i= istart, iend
        isum = isum + i
    enddo

    call MPI_ALLREDUCE(isum,itot,1,MPI_INTEGER8,MPI_SUM,MPI_COMM_WORLD,ierr)
    write(6,10) 'node ',irank,' itot =',itot, ' isum =',isum
    10 format(A,2x,I2,2x,A,I16,2x,A,I16)
    call MPI_FINALIZE(ierr)
end program allreduce
```

Applications

- ▣ Monte Carlo PI Calculation
- ▣ Molecule energy minimization
 - Master / Worker model

Exercise : (Monte Carlo PI calculation)



PI=3.141592...

$$\pi = 4 \frac{N_{in_circle}}{N_{tpoints}}$$

Follow exercise note !

% qsub -I -q n4 -N [your account]

* pi_mc.f90


```
program pi_mc
  use mpi
  implicit none
  real*8, parameter :: PI25DT=3.141592653589793238462643d0
  integer tpoints
  integer istart, iend, in_circle, in_tot
  integer irank, nprocs, i, ierr
  real*8 :: pi, x,y,r
  real*4 :: time_before, time_after, time_elap,time_tot
  real*8 :: stime, etime, ttime
  integer :: iseed = 123
  call MPI_INIT( ierr )
  call MPI_COMM_RANK( MPI_COMM_WORLD, irank, ierr )
  call MPI_COMM_SIZE( MPI_COMM_WORLD, nprocs, ierr )
  if ( irank == 0 ) then
    write(6,'(A)') 'Monte Carlo PI Calculation...'
    write(6,'(A,$)') 'Enter the number of tpoints = '
    read *, tpoints
    print *, 'Total tpoints      = ',tpoints
  endif
  call MPI_BCAST(tpoints,1,MPI_INTEGER,0,MPI_COMM_WORLD,ierr)
  call para_range(1,tpoints, nprocs, irank, istart, iend)
```

* pi_mc.f90


```
in_circle = 0
iseed = iseed + irank
stime = MPI_WTIME ()
call cpu_time (time_before)
do i = istart, iend
  x = ran(iseed)-0.5
  y = ran(iseed)-0.5
  r = sqrt(x*x + y*y)
  if (r<0.5) in_circle = in_circle + 1
enddo
call cpu_time (time_after)
etime = MPI_WTIME ()
ttime = etime - stime
time_elap = time_after- time_before
call MPI_REDUCE(in_circle,in_tot,1,MPI_INTEGER,MPI_SUM,0,MPI_COMM_WORLD,ierr)
call MPI_REDUCE(time_elap,time_tot,1,MPI_REAL,MPI_SUM,0,MPI_COMM_WORLD,ierr)
write(6,'(A,I4,A,I16)') ' irank = ',irank, ' in_circle= ', in_circle
if (irank == 0) then
  pi = 4.0*in_tot/tpoints
  print *, 'pi=',pi, ' error=',dabs(PI25DT-pi)
  print *, 'Total in_circle=',in_tot, ttime, ' seconds'
  print *, 'Total cpu time = ',time_tot, ' seconds'
  print *, 'speed up      = ',time_tot/ttime
endif
call MPI_FINALIZE (ierr)
end program pi_mc
```

Molecule energy minimization


Met-enkephalin (TYR-GLY-GLY-PHE-MET)



$$E = \frac{1}{2} \sum_{\text{bonds}} k_b (b - b_0)^2 + \frac{1}{2} \sum_{\text{bonds}} k_\theta (\theta - \theta_0)^2 + \sum_{\text{dihedral angles}} k_\phi \cos(n\phi - \delta) + \sum_{ij} \left(\frac{A_{ij}}{r_{ij}^6} + \frac{B_{ij}}{r_{ij}^{12}} + \frac{C_{ij}}{r_{ij}^{10}} \right) + \sum_{ij} \frac{q_i q_j}{\epsilon r_{ij}}$$



$E(x_1, x_2, \dots, x_n)$



```
module inimodel
  save
  real*8, allocatable :: xyz(:, :)
end module inimodel
```

* project/tinker/source/nmin.f90

```
program nmin
  use mpi
  use inimodel
  implicit none
  include 'sizes.i'
  include 'atoms.i'
  include 'sequen.i'
  include 'inform.i'
  include 'argue.i'
  include 'zcoord.i'
  real*8, allocatable :: ene(:)
  real*8, allocatable :: bank(:, :, :)
  integer mode
  integer ierr, irank, nprocs
  integer nconf, i, j, k

  call initial
  call getxyz
  call mechanic
  allocate (xyz(3, n))
  forall (i=1:n) ! copy initial model
    xyz(:, i) = (/ x(i), y(i), z(i) /)
  end forall
  call MPI_INIT( ierr )
  call MPI_COMM_RANK( MPI_COMM_WORLD, irank, ierr )
  call MPI_COMM_SIZE( MPI_COMM_WORLD, nprocs, ierr )

  if (irank == 0) then
    write(6, '(A,$)') 'Enter the number of conformation to minimize ='
    read *, nconf
    allocate(ene(nconf), bank(3, n, nconf))
  endif

  if (irank == 0) then
    call feedin (nconf)
  else
    call minim (nconf)
  endif
end if
```

```

subroutine feedin (nconf)
  implicit none
  include 'sizes.i'
  include 'atoms.i'
  integer nconf
  integer istat(MPI_STATUS_SIZE)
  integer i,j,k,l,mm,id, ierr, man
  integer idum
  mm = 0
  do id=1, min(nprocs,nconf)
    mm = mm + 1
    call mpi_send(mm,mpi_integer4,mm,123,mpi_comm_world,ierr)
  enddo

  do id=1, nconf
    call mpi_recv(k,1,mpi_integer4,mpi_any_source,123,
      mpi_comm_world,istat,ierr)
    man = istat(mpi_source)
    call mpi_recv(ene(k),1,mpi_real8,man,234,
      mpi_comm_world,istat,ierr)
    call mpi_recv(bank(:, :, k), 3*n, mpi_real8, man, 345,
      mpi_comm_world,istat,ierr)

    if (mm < nconf) then
      mm = mm + 1
      call mpi_send(mm,1,mpi_integer4,man,123,
        mpi_comm_world,ierr)
    else
      call mpi_send(0,1,mpi_integer4,man,123,
        mpi_comm_world,ierr)
    endif
  enddo
end subroutine feedin

```

```


subroutine minim (nconf)
  implicit none
  include 'sizes.i'
  include 'atoms.i'
  integer istat(MPI_STATUS_SIZE)
  integer id,ierr, nconf
  integer i,j, idum
  real ran1, ranum
  real*8 e
  real*8 xyz(3,n)

  idum = 123 + irank

  if (irank > nconf) return
  do
    call mpi_recv(id,1,mpi_integer4,0,123,
      mpi_comm_world,istat,ierr)
    if (id == 0) return
    ranum = ran1 (idum)
    call randomize (idum)
    call minimize (e)
    forall (i=1:n)
      xyz(1,i) = x(i); xyz(2,i) = y(i); xyz(3,i) = z(i)
    end forall
    call mpi_send(id,1,mpi_integer4,0,123,mpi_comm_world,ierr)
    call mpi_send(e,1,mpi_real8,0,234,mpi_comm_world,ierr)
    call mpi_send(xyz,3*n,mpi_real8,0,345,mpi_comm_world,ierr)
  enddo
end subroutine minim

```

* 20 minimized models



b004.pdb	Total Energy=	-56.020190
b003.pdb	Total Energy=	-56.183630
b008.pdb	Total Energy=	-56.270449
b019.pdb	Total Energy=	-56.318451
b013.pdb	Total Energy=	-56.336022
b001.pdb	Total Energy=	-56.338882
b011.pdb	Total Energy=	-56.338927
b014.pdb	Total Energy=	-56.341662
b012.pdb	Total Energy=	-56.342432
b005.pdb	Total Energy=	-56.342932
b018.pdb	Total Energy=	-56.343037
b016.pdb	Total Energy=	-56.343071
b006.pdb	Total Energy=	-56.343181
b017.pdb	Total Energy=	-56.343955
b002.pdb	Total Energy=	-56.344669
b010.pdb	Total Energy=	-56.345870
b015.pdb	Total Energy=	-56.345952
b009.pdb	Total Energy=	-56.609061
b020.pdb	Total Energy=	-57.016739
b007.pdb	Total Energy=	-57.106061

Advanced Course

- Derived Type
- Grouping and Virtual Topology
 - MPI provides routines to provide structure to collections of processes
- MPI-2
 - One-side communication
 - Dynamic process
 - Parallel I/O

Summary

- 6 Function of MPI library
- Point to Point Communication
- Collective Communication

MPI 프로그래밍 생각할 점

- 시리얼 프로그램: 시간이 얼마나 걸리는가?
- 병렬컴퓨터에 대해서 알아야 한다
 - CPU 구성
 - 메모리 상황
 - 네트워크 성능
- 풀고 싶은 문제의 특성을 알아야 한다
 - 문제가 쉽게 병렬로 될 수 있는 것인지?
 - Load Balancing
 - 커뮤니케이션 문제

Acknowledgement

Home page: <http://cac.kias.re.kr>



CAC 거대수치계산연구센터
KIAS CENTER FOR ADVANCED COMPUTATION

- Director Professor **Changbom Park**
- Research Professor **Juhan Kim**
- Research Professor **Keehyoung Joo**
- Computer Administrator **Kyoungsoo Kim**
- Administration Staff **Minjung Choi**
- Assisting developer **Jinsun Kang**

`` Only love has no limits. In contrast, our predictions can fail, our communication can fail, and our knowledge can fail. For our knowledge is patchwork, and our predictive power is limited. **But when perfection comes, all patchwork will disappear.** ``

(1 Cor. 13:8-10)

